







DESCRIPTION:

- External mini projector / spike luminaire,
- Body made of die-cast aluminium with electro-coating static paint in matt finish.
- Diffuser made of clear tempered glass, thermal shock resistant
- Reflector made of polished anodized aluminium
- High corrosion resistance capability.
- Silicon rubber gasket for dust and waterproof
- High efficient CREE LED
- Stainless steel alloy screws
- Power supply: 240V/60Hz
- Heat resistant and solid conduct wiring
- Ideal for External lighting
- European standard of EN 60598




Model:	BR1650-M	BR1650-L	BR1750-M	BR1750-L
Power	10W/12W/15W	20W/25W	5W/10W	9W/12W/18W/24W
Input Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V
CRI	≥80	≥80	≥80	≥80
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W
Color Temp.	2700-6500K	2700-6500K	2700-6500K	2700-6500K
	RGB	RGB	RGB	RGB
Power Factor	>0.9	>0.9	>0.9	>0.9
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Drive	Meanwell			
Dimension	92x110x180mm	125x140x250mm	105x95x220mm	150x120x265mm
Life Span	45000 - 50000Hrs			



PHOTOMETRIC DATA

Light Distribution Curve [Unit: cd]



Lux distance Curve

Center Beam LUX	Beam Width	
	V	H
511.69 LUX	1.4m	1.3m
127.92 LUX	2.7m	2.6m
56.85 LUX	4.1m	3.9m
31.98 LUX	5.4m	5.2m
20.47 LUX	6.8m	6.6m
14.21 LUX	8.2m	7.9m

Vert Spread: 37.6 Horiz Spread: 36.3

BEAM ANGLE



Available:

