





BRTGDX-72




DESCRIPTION:

Surface mounted LED projector for external use
 Body made of die-cast aluminium with polyester powder coated finish.
 Epoxy cationic electro-coating, upon phospho-chromate treatment, Uv-stabilising primer.
 Diffuser made of tempered glass, thermal shock and impact resistant.
 Adjustable mounting bracket
 Stainless steel cable gland
 High corrosion resistant capability
 High quality LED Chip, CREE / PHILIPS SMD3030
 - Heat resistant and solid conduct wiring
 - Ideal for External lighting
 - European standard of EN 60598


BRTGDX-150



BRTGDX-200



Available:



High quality SMD LED



Adjustable Bracket



Die-cast aluminium body



High quality driver



Stainless Steel Screw



Heat Sink

Product Code	BRTGDX-40	BRTGDX-50	BRTGDX-60	BRTGDX-72	BRTGDX-150	BRTGDX-200
Rated Power	40W LED	50W LED	60W LED	72W LED	150W LED	200W LED
LED Type	CREE, 48PCS	CREE, 48PCS	CREE, 48PCS	CREE, 48PCS	CREE, 72PCS	CREE, 108PCS
Luminous Flux	120lm/W	120lm/W	120lm/W	120lm/W	120lm/W	120lm/W
Input Voltage	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V	AC220-240V
Frequency Range	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz
Color Rendering Index	>80	>80	>80	>80	>80	>80
Power Factor	>0.90	>0.90	>0.90	>0.90	>0.90	>0.90
Efficiency	>89%	>89%	>89%	>89%	>89%	>89%
Color Temperature	2700K - 6500K / RGB	2700K - 6500K / RGB	2700K - 6500K / RGB	2700K - 6500K / RGB	2700K - 6500K / RGB	2700K - 6500K / RGB
Beam Angle	15 / 25 / 45 / 60°	15 / 25 / 45 / 60°	15 / 25 / 45 / 60°	15 / 25 / 45 / 60°	15 / 25 / 45 / 60°	15 / 25 / 45 / 60°
Temperature in Working	-35°C +65°C	-35°C +65°C	-35°C +65°C	-35°C +65°C	-35°C +65°C	-35°C +65°C
Size	Dia:236xH215mm	Dia:236xH215mm	Dia:236xH215mm	Dia:236xH215mm	Dia:280xH255mm	Dia:325xH285mm
Protection Grade	IP65	IP65	IP65	IP65	IP65	IP65
Life Span	50000Hrs					

Photometric Data

