



**DESCRIPTION:**

Mini LED Projector for external lighting,  
 Body made of die-cast aluminium, aluminium alloy with Polyester powder coated finish.  
 Epoxy cationic electro-coating, upon phospho-chromate treatment, Uv-stabilising primer.  
 Diffuser made of clear tempered glass, thermal shock resistant  
 Adjustable light angle 90° - vertical.  
 High corrosion resistance capability.  
 Silicon rubber gasket for dust and waterproof  
 High efficient CREE / EPISTAR / PHILIPS LED  
 Compatible with DMX Controller system  
 Stainless steel alloy screws  
 Power supply: 165V-240V/60Hz  
 - Heat resistant and solid conduct wiring  
 - Ideal for External Garden and Elevation lighting  
 - European standard of EN 60598



Model:	BSLP-(**)	BSLP-(**)	BSLP-(**)	BSLP-(**)
Power	3x1-3W	5x3W / 9x1W / 9x2W	16x1W / 16x2W	16x3W
Input Voltage	DC24V/AC220V	DC24V/AC220V	DC24V/AC220V	DC24V/220V
CRI	≥80	≥80	≥80	≥80
Luminous Flux	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W
Color Temp.	2700-6500K/RGB	2700-6500K/RGB	2700-6500/RGB	2700-6500K/RGB
Power Factor	>0.95	>0.95	>0.95	>0.95
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Humidity	<95%	<95%	<95%	<95%
Dimension	70x70x85mm	95x95x105mm	125x125x120mm	145x145x120mm
Life Span	45000 - 50000Hrs			

- AC220V Version supplied with builtin LED Drive.  
 - DC24V/12V Version required Remote Drive.

