




S-2061




























## **DESCRIPTION:**

External garden or walkway bollard luminaire, Body made of die-cast alumnium with polyester powder Coated finish.

Epoxy cationic electro-coating, upon phospho-chromate Treatment, Uv-stabilising primer

Diffuser made of tempered glass, thermal shock and Impact resistant.

High corrosion resistant capability Silicon rubber gasket for dust & water proof

Stainless steel alloy screws.

Power supply: AC85-220V/50-60Hz

- -Heat resistant and solid conduct wiring
- -Ideal for external Garden and Area lighting
- -European standard of EN 60598

















Model	S-2061A / S-2061B / S-2061C					S-2061C	
Power	10W LED	12W LED	15W LED	18W LED	20W LED	25W LED	30W LED
LED Type	СОВ	СОВ	СОВ	СОВ	СОВ	СОВ	СОВ
Input Voltage	AC85-220V/50-60Hz	AC85-220V/50-60Hz	AC85-220V/50-60Hz	AC85-220V/50-60Hz	AC85-220V/50-60Hz	AC85-220V/50-60Hz	AC85-220V/50-60Hz
CRI	<u>&gt;</u> 80	≥80	≥80	≥80	<u>&gt;</u> 80	<u>&gt;</u> 80	<u>&gt;</u> 80
Luminous Flux	110-120LM/W	110-120LM/W	110-120LM/W	110-120LM/W	110-120LM/W	110-120LM/W	110-120LM/W
Color Temp	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
Temp. in Working	-40℃ +65℃	-40℃ +65℃	-40℃ +65℃	-40°C +65°C	-40°C +65°C	-40°C +65°C	-40°C +65°C
Protection	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Life Span	50000Hrs					50000Hrs	

## PHOTOMETRIC DATA

