




BD400S-20/25/30



Surface Finish:



DESCRIPTION:

- Surface mounted LED Downlight for interior use
- Body made of aluminium alloy, powder coated, high corrosion resistance capability.
- Tempered glass diffuser
- Polished anodized aluminium reflector
- Aluminium structured heat sink housing.
- Stainless steel alloy screws
- Dimmable DALI/TRIAC 0 - 10V/PWM available
- Power supply: 85V-265V/60Hz
- Heat resistant wiring
- Ideal for internal use
- European standard of EN 60598

Model:	BD400S-5	BD400S-10	BD400S-15	BD400S-20	BD400S-25	BD400S-30
Power	5W LED	10W LED	15W LED	20W LED	25W LED	30W LED
LED Type	COB	COB	CCB	COB	COB	COB
Input Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V	AC85-265V	AC85-265V
CRI	>80	>80	>80	>80	>80	>80
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W	100LM/W	100LM/W
Color Temp.	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Beam Angle	25/45/60°	25/45/60°	25/45/60°	25/45/60°	25/45/60°	25/45/60°
Size	95x95x145mm	120x120x160mm	120x120x160mm	150x150x160mm	150x150x160mm	150x150x160mm
Life Span	50000 Hrs					

