



DESCRIPTION:

External garden or walkway bollard luminaire,
Body made of die-cast aluminium with polyester powder
Coated finish.

Epoxy cationic electro-coating, upon phospho-chromate
treatment, Uv-stabilising primer

Diffuser made of vandal resistant, V2 self extinguishing,
Uv-stabilized polycarbonate, clear glass

High corrosion resistant capability

Silicon rubber gasket for dust & water proof
Stainless steel alloy screws.

High quality LED chip by Bridgelux

Power supply: AC100-240V/50Hz

-Heat resistant and solid conduct wiring

-Ideal for external garden and area lighting

-European standard of EN 60598

Available:



Model No:	S-9100S			S-9100L				
	5W LED	8W LED	10W LED	10W LED	14W LED	18W LED	24W LED	30W LED
Power	5W LED	8W LED	10W LED	10W LED	14W LED	18W LED	24W LED	30W LED
LED Type	COB	COB	COB	COB	COB	COB	COB	COB
Voltage	AC100-240V / 50-60Hz			AC100-240V / 50-60Hz				
Luminous Flux	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W
Color Temperature	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K	3000 - 6500K
CRI	>80	>80	>80	>80	>80	>80	>80	>80
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
Working Temp	-30 ~ +50°C	-30 ~ +50°C	-30 ~ +50°C	-30 ~ +50°C	-30 ~ +50°C	-30 ~ +50°C	-30 ~ +50°C	-30 ~ +50°C
Protection	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Life Span	50000Hrs			50000Hrs				