



Protection: IP65

Special version shall be provided on request



DESCRIPTION:

External decorative lighting pole,
 Body made of high quality aluminium alloy with Polyester powder coated finish.
 Epoxy cationic electro-coating, upon phospho-chromate Treatment, Uv-stabilising primer.
 Diffuser made of Uv-stabilised polycarbonate
 Louver made of anodized aluminium
 High corrosion resistant capability
 silicon rubber gasket for dust & waterproof
 Stainless steel alloy screws
 Power supply: 240V/50Hz
 - Heat resistant and solid conduct wiring
 - Ideal for external garden and area lighting
 - European standard of EN 60598

PHILIPS LUXEON - 3030 2D UNIT



Model	S-7008A/B/C				
	40W LED	65W LED	80W LED	100W LED	120W LED
Power	40W LED	65W LED	80W LED	100W LED	120W LED
LED Type	PHILIPS, SMD3030	PHILIPS, SMD3030	PHILIPS, SMD3030	PHILIPS, SMD3030	PHILIPS, SMD3030
Voltage	AC100-277V / 50Hz	AC100-277V / 50Hz	AC100-277V / 50Hz	AC100-277V / 50Hz	AC100-277V / 50Hz
CRI	>80	>80	>80	>80	>80
Power Factor	>90	>90	>90	>90	>90
Luminous Flux	110LM/W	110LM/W	110LM/W	110LM/W	110LM/W
Color Temperature	3000K-6500K	3000K-6500K	3000K-6500K	3000K-6500K	3000K-6500K
Temp in Working	-25°C + 50°C	-25°C + 50°C	-25°C + 50°C	-25°C + 50°C	-25°C + 50°C
Life Span	50000hrs				

Custom made wattage and multi number of luminers can be adopted as per the request

S-7008A/B/C

