



**DESCRIPTION:**

Surface mounted weatherproof bulkhead luminaire, Body made of die-cast aluminium with polyester powder coated finish.

Epoxy cationic electro-coating, upon phosphochromate treatment, Uv-stabilising primer.

Diffuser made of tempered frosted glass, thermal shock and impact resistant.

High corrosion resistant capability

Silicon rubber gasket for dust proof

Stainless steel alloy screws

-Heat resistant and solid conduct wiring

-Ideal for external elevation lighting

-European standard of EN 60598

**LAMP OPTION**

SOCKET	WATTAGE
E27	1x15W - 22W CFL
G23	1x9W - 11W TC-S
G24	1x9W - 18W TC-D
LED-E27	1X13W LED Max.
LED-G24D	1X13W LED Max.

LED Spec	1012S	1012L
Rated Power	18W LED	24W LED
LED Type	SMD LED	SMD LED
Input Voltage	AC165-245V	AC165-245V
Frequency Range	50Hz-60Hz	50Hz-60Hz
Power Factor	>0.95	>0.95
Color Temperature	2700K-6500K	2700K-6500K
Color Rendering Index	>80	>80
Mini Luminous Flux	110LM/W	110LM/W
Temp. in Working	20°C +50°C	20°C +50°C
Protection Grade	IP65	IP65
Life Span	50000Hrs	



**BROADWAY - UK Ltd.**