



#### DESCRIPTION:

Surface mounted weatherproof bulkhead luminaire, Body made of die-cast aluminium with polyester powder coated finish.

Epoxy cationic electro-coating, upon phosphochromate treatment, Uv-stabilising primer.

Diffuser made of tempered, thermal shock and impact resistant frosted glass.

Opal polycarbonate diffuser on request

High corrosion resistant capability

Silicon rubber gasket for dust proof

Stainless steel alloy screws

Power supply: 240V/50Hz

-Heat resistant and solid conduct wiring

-Ceramic lamp holder "E27"

-Ideal for external elevation lighting

-European standard of EN 60598

#### LAMP OPTION

SOCKET	WATTAGE
E27	1x15W - 22W CFL
G23	1x9W - 11W TC-S
G24	1x9W - 18W TC-D
LED-E27	1X12W LED
LED-G24D	1X11W LED

LED Spec		
Rated Power	18W LED	20W LED
LED Type	SMD LED	SMD LED
Product Size	L251xW160xH94mm	251x160x94mm
Input Voltage	AC220-240V	AC220-240V
Frequency Range	50Hz-60Hz	50Hz-60Hz
Power Factor	>0.95	>0.95
Color Temperature	2700K-6500K	2700K-6500K
Color Rendering Index	80-90	80-90
Mini Luminous Flux	135LM/W	135LM/W
Temp. in Working	20°C +50°C	20°C +50°C
Protection Grade	IP65	IP65
Life Span	50000Hrs	

