




SMEW36-12



DESCRIPTION:

Semi-Recessed mounted buried focusing luminaire for symmetric Or asymmetric angle.

Housing made of die-cast aluminium, powder coated, high Corrosion resistance capability.

Frame made of solid stainless steel (A2=316)

Tempered clear / frosted glass diffuser

Honeycomb louvre available on request (HCL)

High corrosion resistance capability.

Stainless steel gland, IP67

Silicon gasket for dust and waterproofing


Stainless steel alloy screws

Power supply: 220V-240V/50Hz


- Heat resistant and solid conduct wiring
- Ideal for external garden, facade lighting
- European standard of EN 60598



SMEW36-24



SMEW36-36




MODE	SMEW36-12	SMEW36-24	SMEW36-36
LED	Epistar / CREE	Epistar / CREE	Epistar / CREE
Power	12W 24W LED	12W - 24W LED	12W - 24W LED
Size	D222xH127mm	D260xH151mm	D320xH151mm
Input Voltage	DC12V / DC24V / 240V		
CRI	>80	>80	>80
Efficiency	>89%	>89%	>89%
Luminous Flux	100LM/W	100LM/W	100LM/W
Color Temp.	2700 6500k	2700 6500k	2700 6500k
Power Factor	>0.9	>0.9	>0.9
Temp. in Working	20°C + 50°C	20°C + 50°C	20°C + 50°C
Drive	HF Electronic / DALI Dimmable		
Life Span	50000Hrs		




Honeycomb Louver

Order Code: HCL




PHOTOMETRIC DATA


16W MEDIUM BEAM




16W WIDE BEAM




22W MEDIUM BEAM



22W WIDE BEAM



35W NARROW BEAM



35W MEDIUM BEAM

