




B31655-R/S



B31670-R/S



Power Cable:

- H05RN-F 2X1.0mm² L=0.5M (low voltage)
- H05RN-F 3X0.75mm² L=0.5M (high voltage)
- H05RN-F 5X0.5mm² L=0.5M (RGB 3 in 1, RGB 4 in 1)


Beam Angle:



Available:



Mounting Sleeve



DESCRIPTION:

- Recessed mounted mini buried uplight with PC mounting sleeve for easy installation.
- Body made of die-cast aluminium in powder coated finish
- Frame made of solid stainless steel (316 grade)
- Tempered clear glass diffuser
- High corrosion resistance capability.
- silicon gasket for dust and water proofing.
- Stainless steel alloy screws.
- Power supply 220V-240V/50Hz
- Heat resistant wiring
- Ideal for display and deck lighting
- European standard of EN 60598

Product Code	B31655-R/S	B31670-R/S
Rated Power	2W / 3W / 4W / 5W	
LED Type	CREE / OSRAM / EPSTAR	
Product Size	DIA: 55x55x82mm	DIA: 70x70x82mm
Input Voltage	AC220 -240V / 12V / 24V	
Frequency Range	50Hz-60Hz	50Hz-60Hz
Power Factor	>0.95	>0.95
Color Temperature	2700K-6500K / RGB	2700K-6500K / RGB
Control Mode	RGB 3 in 1 / RGB 4 in 1, DMX512	
Color Rendering Index	>80	>80
Mini Luminous Flux	100LM/W	100LM/W
Beam Angle	10/25/35/45/60°	10/25/35/45/60°
Temp. in Working	20°C +50°C	-20°C +50°C
Protection Grade	IP67	IP67
Life Span	50000Hrs	