



DESCRIPTION:

External elevation or garden luminaire,
 Body made of extruded in titanium finish, black, grey, and White available in powder coated by electro-coating static Paint in matt finish.

ART: BR-700212CR2, body made of die-cast aluminium in Black, grey, silver, white finish.

Adjustable light angle in horizontal 360° and vertical 120°
 Diffuser made of clear tempered glass, thermal shock resistant.

High corrosion resistance capability.

Silicon rubber gasket for dust and waterproof

High efficient CREE LED



Stainless steel alloy screws

Power supply: 220V-240V/60Hz

- Heat resistant and solid conduct wiring

- Ideal for external garden and wall wash lighting

- European standard of EN 60598



Model:	BR-700212-3W	BR-700212-5W	BR-700212-7W	BR-700212CR-10W	BR-700212CR-12W	BR-700212CR-15W	BR-700212CR-18W	BR-700212CR-20W
				BR-700212CR2-10W	BR-700212CR2-12W	BR-700212CR2-15W	BR-700212CR2-18W	BR-700212CR2-20W
Power	3W LED	5W LED	7W LED	10W LED	12W LED	15W LED	18W LED	20W LED
Input Voltage	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V	AC220V-240V
CRI	>80	>80	>80	>80	>80	>80	>80	>80
Luminous Flux	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W	100-110LM/W
Color Temp.	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K	3000-6500K
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Humidity	<95%	<95%	<95%	<95%	<95%	<95%	<95%	<95%
Dimension	60x93mm	60x93mm	60x93mm	100x145mm	100x145mm	100x145mm	100x145mm	100x145mm
Life Span	45000 - 50000Hrs							