





## DESCRIPTION:

- External mini projector / spike luminaire,
- Body made of die-cast aluminium with electro-coating static paint in matt finish.
- Diffuser made of clear tempered glass, thermal shock resistant
- Reflector made of polished anodized aluminium
- High corrosion resistance capability.
- Silicon rubber gasket for dust and waterproof
- High efficient CREE LED
- Stainless steel alloy screws
- Power supply: 240V/60Hz
- Heat resistant and solid conduct wiring
- Ideal for External lighting
- European standard of EN 60598




Model	TGD100-10W TGD200-10W	TGD100-12W TGD200-12W	TGD100-15W TGD200-15W	TGD100-20W TGD200-20W
Power	10W LED	12W LED	15W LED	20W LED
Input Voltage	AC220-240V	AC220-240V	A220-240V	AC220-240V
CRI	>80	>80	>80	>80
Luminous Flux	100LM/W	100LM/W	100LM/W	100LM/W
Color Temp.	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Power Factor	>0.9	>0.9	>0.9	>0.9
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Drive	Meanwell			
Protection Grade	IP65	IP65	IP65	IP65
Life Span	45000 - 50000Hrs			



## PHOTOMETRIC DATA

Light Distribution Curve [Unit: cd]



Lux distance Curve

Center Beam LUX	Beam Width	
	V	H
511.69 LUX	1.4m	1.3m
127.92 LUX	2.7m	2.6m
56.85 LUX	4.1m	3.9m
31.98 LUX	5.4m	5.2m
20.47 LUX	6.8m	6.6m
14.21 LUX	8.2m	7.9m

Vert.Spread:37.6 Horiz.Spread:36.3

Available:



## BEAM ANGLE



With Cap



Base



Spike Kit