





BDP08-90



BDP08-260



## DESCRIPTION

Modern and classical lighting Pole luminaire, Body made of stainless steel with electro static Powder coated painting in black, grey or silver Finish. Epoxy cationic electro-coating, upon phospho-Chromate treatment, Uv-stabilising primer. Diffuser made of Translucent fluted acrylic. High corrosion resistant capability Silicon rubber gasket for dust & waterproof Stainless steel alloy screws

- Heat resistant and solid conduct wiring
- Ideal for external garden and area lighting
- European standard of EN 60598

## Color Options



Model No	BDP08			
Power	5W LED	10W LED	15W LED	20W LED
LED Type	SMD	SMD	SMD	SMD
Voltage	AC220-240V	AC220-240V	AC220-240V	AC220-240V
Luminous Flux	90-100lm/w	90-100lm/w	90-100lm/w	90-100lm/w
Color Temperature	3000K - 6500K	3000K - 6500K	3000K - 6500K	3000K - 6500K
CRI	>90	>90	>90	>90
Power Factor	>0.9	>0.9	>0.9	>0.9
Working Temp	-30°~+50° C	-30°~+50° C	-30°~+50° C	-30°~+50° C
Protection	IP65	IP65	IP65	IP65
Life Span	50000Hrs			

Note: Custom wattage and size available on request.

## Photometric Data

