




DESCRIPTION:

- Recessed mounted LED downlight with high quality electronic drive.
- Body made of die-cast aluminium in electro powder coated.
- Reflector made of polished hammered high gloss for glare free lighting distribution.
- Diffuser made of clear glass or semi frosted, Uv-stabilized and thermal shock resistant.
- Mounting clamp in galvanized plate for easy installation and maintenance.
- Heat dissipating aluminium housing
- Heat resistant and solid conduct wiring
- Philips / Bridgelux LED
- Ideal for Office, Showroom, other public areas
- European standard of EN 60598




Available:




1. Cut a hole in the ceiling according to the size in the instruction.









2. Switch off power supply, and put the driver in it; plug into the mains.



3. Connect DC joint, make sure close connecting, no loosening.



4. Press and hold the spring, and push the lamp into the ceiling; make sure no loosening, then power on.



Model No.	BR031B-3	BR031B-5	BR031B-10	BR031B-15	BR031B-20	BR031B-30
Power	3W LED	5W LED	10W LED	15W LED	20W LED	30W LED
LED Type	COB	COB	COB	COB	COB	COB
Dimension	Dia:90xH:42mm	Dia:105xH:42mm	Dia:130xH:42mm	Dia:165xH:60mm	Dia:190xH:60mm	Dia:225xH:60mm
Voltage	AC160V-245V	AC160V-245V	AC160V-245V	AC160V-245V	AC160V-245V	AC160V-245V
Power Factor	>0.90	>0.90	>0.90	>0.90	>0.90	>0.90
Color Temp.	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K
CRI	≥80	≥80	≥80	≥80	≥80	≥80
Luminous Flux	100-120LM/W	100-120LM/W	100-120LM/W	100-120LM/W	100-120LM/W	100-120LM/W
Temp. in Working	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C	-30°C +50°C
Protection	IP54	IP54	IP54	IP54	IP54	IP54
Dimmable	TRIAC/0-10V/PWM/Dali Dimmable (Order code = / Dali Dim / PWM Dim)					
Life Span	50000Hrs					