


BR1015-(**)



DESCRIPTION:

Recessed mounting focusing eye ball luminaire.
 Suitable for symmetrical and assymetrical lighting
 Body made of die-cast aluminium with Powder coated in Black, white and silver finish.
 Anodized aluminium reflector epoxy coated fiber in Black, white & silver finish.
 High corrosion resistant capability
 Excellent heat dissipation.
 High efficient COB LED chip by CREE / Philips / Bridgelux.
 Dimmable DALI / TRIAC 0-10V available on request.
 -Heat resistant and solid conduct wiring
 -Ideal for office & interior lighting.
 -European standard of EN 60598

Available



Product Code	BR1015-5	BR1015-10	BR1015-15	BR1015-30	BR1015-40
Rated Power	5W - 10W LED	10W - 15W LED	15W - 20W LED	30W LED	40W LED
LED Type	COB	COB	COB	COB	COB
Input Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Lumen	100LM/W	100LM/W	100LM/W	100LM/W	100LM/W
Color Rendering Index	≥80	≥80	≥80	≥80	≥80
Power Factor	>0.90	>0.90	>0.90	>0.90	>0.90
Color Temperature	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K	2700K - 6500K
Beam Angle	15°/ 30°/ 45°	15°/ 30°/ 45°	15°/ 30°/ 45°	15°/ 30°/ 45°	15°/ 30°/ 45°
Temperature in Working	-30°C~+50°C	-30°C~+50°C	-30°C~+50°C	-30°C~+50°C	-30°C~+50°C
Dimmable	TRIAC/0-10V/PWM/Dali Dimmable				
Size	Ø90xH80mm	Ø114xH95mm	Ø138x120mm	Ø165xH145mm	Ø190xH130mm
Life Span	50000 - 60000Hrs				



BROADWAY - UK Ltd.