




BR-1X5100



DESCRIPTION

Body made of aluminium alloy with electro static Powder coated painting in custom driftwood grey finish. Epoxy cationic electro-coating, upon phospho-chromate Treatment, UV-stabilizing primer. Luminaire diffuser made of tempered clear glass thermal Shock and impact resistant. Lantern cage in alluminum alloy with resistant clear glass. High corrosion resistant capability Silicon rubber gasket for dust & water proof Stainless steel alloy screws. Power supply: AC85-265V/50Hz
-Heat resistant and solid conduct wiring
-Ideal for external garden and pathway lighting
-European standard of EN 60598

Available:



BR-2X5100



Model No	BR-1X5100				BR-2X5100	
Power	1x8W+1W LED	1x10W+1W LED	1x15W+1W LED	2x8W+1W LED	2x10W+1W LED	2x15W+1W LED
LED Type	COB+E27	COB+E27	COB+E27	COB+E27	COB+E27	COB+E27
Voltage	AC85-265V / 50-60Hz					
Luminous Flux	100-120lm/w	100-120lm/w	100-120lm/w	100-120lm/w	100-120lm/w	100-120lm/w
Color Temperature	3000K - 6500K	3000K - 6500K	3000K - 6500K	3000K - 6500K	3000K - 6500K	3000K - 6500K
CRI	>80	>80	>80	>80	>80	>80
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95	>0.95
Working Temp	-30°~+50°C	-30°~+50°C	-30°~+50°C	-30°~+50°C	-30°~+50°C	-30°~+50°C
Protection	IP65	IP65	IP65	IP65	IP65	IP65
Life Span	50000Hrs					

